

Quadra Plus Sparkling Specification Sheet

Instant boiling, chilled and sparkling system with sink mixer tap



"Featuring a separate mixer tap complete with its own hot water supply, functioning as your hot water service and still providing boiling, chilled and sparkling filtered drinking water"



Boiling Water Reserve

All Quadra Plus units have a boiling water reserve to ensure that you can still have boiling water for drinking, even after the hot water to the mixer tap is fully drawn.

Adjustable Professional Saturated Sparkling

The CO² injection system ensures the saturation of CO² in the water is high which means it has better life, and consequently taste.

General Health Benefits

The Billi Quadra Plus Sparkling system includes a silver Ion (Ag+) system which benefits the health of the user and the unit as it eliminates the potential for growth of harmful bacteria.



Safety First

The Billi SplashFree™ boiling water delivery electronically varies the water flow, slowing momentarily to eliminate splashing as the water first enters the cup. All Billi dispensers are supplied standard with a safety switch.

Cupboard Configuration Options

The Quadra Plus Sparkling system is supplied as two modules enabling multiple cupboard configuration to maximise use and efficiency of your cupboard space.



A simple adjustment allows the chilled water to be raised to 15°C, or lowered to 6°C for perfectly chilled, refreshing drinks, with your required temperature being quickly reached and maintained. The boiling side is set at 98.5°C but can be lowered to suit your preference.

New Unprecedented Tap Range. Billi Quadra Plus Sparkling systems all include the DDA compliant XL tap in 12 stunning and elegant colours. Popular for corporate colour matching. A pin type sink mixer tap or gooseneck sink mixer tap can be specified at the time of order.















Quadra Plus Sparkling Specification Sheet

Specifications and guide to model selection *

*1 cup = 170ml

Product Number		50°C hot water delivery litres per hour	Boiling water delivery cups per hour	Chilled water delivery cups per hour	Current Draw Amps	Height mm	Width mm	Depth mm
90406	Guadra Plus Sparkling	60	180	120	2 x 13	Boiling 340	180	460

Power Supply

Sparkling systems have two modules and require two standard 13a power supplies. All Billi units are supplied with 1m flex cord and plug.

Water Supply

A single 15mm (1/2") inline tap with a male thread should be installed in an easily accessible position. Water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa.

CO² Gas Cylinder

The CO² gas cylinder supplied is 600g. This should be mounted suitable in a well-ventilated area. Each cylinder will provide between 200-350L of sparkling water depending on the chosen setting.

Filtration

Billi premium filters ensure that health threatening pollutants and impurities such as sediment, chemicals, heavy metals, chlorine and pesticides are safely removed leaving you with refreshingly clean drinking water. All Billi cartridges are certified by global public safety agency NSF

International. Filter changes are made simple by our swing change system. Replacement filters and CO^2 cylinders are obtained by calling us direct.


Warranty


All components of the Billi Quadra are covered by a 12 month warranty. This does not include filter cartridges or CO^2 cylinders which are consumables and therefore not covered by warranty.

Certifications

Every Billi drinking water appliance is manufactured under a certified quality control system. The Bill Quadra has been tested and complies with all required standards including: Watermark Licence Number 21525; Tested to AS3498 and AS/NZS4020; Victorian Electrical Safety Act 1998 Approval Number CS1006600V, AS/NZ IS09002; AS1428 Accessibility Design Requirements; Section J6 of the BCA, Certificate Number QEC 11627: C-Tick approved. All filters and connections are WRAS approved.

Preferred installation layout





Advice? Please call us on (02)94581111

